

1. HOT-ROLLED STRUCTURAL STEEL ANGLE (ASTM A36)

PROFILE (LEG X LEG X THICK)	THICKNESS	WEIGHT (LB/FT)	20' BAR WEIGHT	PUNCHED HOLE SPEC	STOCK LENGTHS
1" x 1" x 1/8"	0.125"	0.80 lb	16.0 lb	Plain / Unpunched	1', 2', 6', 10', 15', 20'
1-1/2" x 1-1/2" x 1/8"	0.125"	1.23 lb	24.6 lb	.563" (9/16") on 2" centers (1/2" bolts)	1', 2', 6', 10', 15', 20'
2" x 2" x 1/8"	0.125"	1.65 lb	33.0 lb	.563" on 2" centers (Single / Double)	1', 2', 6', 10', 15', 20'
2" x 3" x 1/4" (L3 x 2 x 1/4)	0.250"	4.10 lb	82.0 lb	Plain / Unpunched	1', 2', 6', 10', 15', 20'
3" x 3" x 1/4"	0.250"	4.90 lb	98.0 lb	Plain / Unpunched	1', 2', 6', 10', 15', 20'
3" x 4" x 1/4" (L4 x 3 x 1/4)	0.250"	5.80 lb	116.0 lb	Plain / Unpunched	1', 2', 6', 10', 15', 20'

2. ROLL-FORMED & GARAGE DOOR PUNCHED ANGLE (AMERICAN STEEL)

PRODUCT TYPE	AVAILABLE LEG SIZES	GAUGE / THICKNESS	PUNCHING PATTERN	FINISH	APPLICATION
Garage Door Punched Angle	1-1/4" x 1-1/4" 1-1/2" x 1-1/2" 2" x 2"	11 ga (1/8") 12 ga (0.105") 14 ga (0.075") 15 ga (0.067")	Punched for 3/8" bolts on 1" centers (both legs)	PRE-GALVANIZED	Overhead door tracks, opener hanging brackets, ceiling supports
Roll-Formed Angle (Punched)	1-1/2" x 1-1/2" 2" x 2"	11 Gauge (approx. 1/8")	.563" holes on 2" centers for 1/2" bolts	PRE-GALVANIZED or Raw	Shelving, equipment racks, bolt-together framing
Roll-Formed Angle (Unpunched)	1-1/2" x 1-1/2" 2" x 2"	11 Gauge (approx. 1/8")	Plain / No Holes	PRE-GALVANIZED or Raw	Edge protection, light structural welding, workbench framing

ORDER FACTORY-DIRECT ONLINE · NO MINIMUM ORDER QUANTITIES

Lengths up to 6 ft ship nationwide via **UPS Ground**. Full lengths up to 20 ft ship LTL Freight.

Visit **steelfront.com** for instant online pricing, CAD specs, and immediate checkout.



SCAN TO ORDER